



VIDEODISPLAY.COM | INFO@VIDEODISPLAY.COM

VID-1502FHD-PM

VID-1502FHD-PM 15.6" Panel Mount Sunlight Readable IP56 FPD

FEATURES

- ☀️ 16:9 Aspect Ratio 1920 x 1080 Resolution
- ☀️ Sunlight Readable 1000 nits Brightness
- ☀️ 344.16 x 193.59 [mm], 13.55 x 7.62 [inch] Display Area
- ☀️ VGA, DVI, HDMI, Composite, Speakers, DisplayPort Input Options
- ☀️ 12VDC, 24VDC Power Options
- ☀️ Rugged Metal Enclosure
- ☀️ Long Shelf Life
- ☀️ Perfect for Kiosk, Equipment and Instrument Drop-In Designs
- ☀️ Compliant with RoHS, UL, CE, FCC, TUV



VID-1502FHD-PM sunlight readable LCD displays provides reliability, durability, and expected longer product life.

The rugged all steel enclosures with robust aluminum alloy front bezel with highly-durable glass (anti-reflective, anti-glare optional) front surface provide the durability needed for demanding industrial environments. Optical bonding done optional between TFT panel and glass/touch panel is available for better visualization in sunlight.

Industrial panel mount monitors come with high brightness LCD flat screen sizes, touchscreen interface, industrial analog & digital driver board, low power consumption, and scratch-resistant capabilities are ideal for system integrators, kiosks, process control, food processing equipment, machine control, human-machine interface, automation equipment, industrial/factory automation, in-vehicle use and marine or indoor, semi-outdoor, outdoor applications.



*Can be used with polarized sunglasses in both landscape and portrait orientations

SPECIFICATIONS

Panel Type	15.6" TFT Active Matrix Panel
Maximum Resolution	1920 x 1080
Pixel Pitch	0.179 (H) x 0.179 (V) [mm]
Contrast Ratio	700:1
Brightness	1000 cd/m ²
Display Area	344.16 x 193.59 [mm] 13.55 x 7.62 [inch]
Response Time	8 ms (Typ.)
Display Colors	16.7 Million
Viewing Angle	140°(H)/120°(V)
Signal Connector	VGA, HDMI, RCA
OSD Control	Power Switch, Menu, Select (+,-), Auto
Operation Temperature	-10°~ 70°C
Storage Temperature	-20°~ 70°C
Power Consumption	32 Watts
Power Supply	External Power Adapter
Safety & EMI	CE, FCC, TUV-GS, UL Compliant
LCD Protection	Glass or Polycarbonate (Options)
Mounting	M4 Panel holes around perimeter of panel VESA Mounting (75/100 mm) on rear
Dimensions	457.2 x 298.45 x 68.58 [mm] 18.00 x 11.75 x 2.70 [inch]
Weight	16 pounds; 6.805 Kilograms



All specifications subject to change without notice

Video Display Corporation
5155 King Street
Cocoa, Florida 32926

MAR 2021

Tel: (321) 784-4427
Fax: (321) 784-6617
<http://videodisplay.com>