



VIDEODISPLAY.COM | INFO@VIDEODISPLAY.COM

VSRMD-1501X

RUGGED 15" Sunlight Readable Marine Display

- 15" COLOR LCD
- RESOLUTION 1024x768
- WIDE VIEWING ANGLE
- 1000 nits, SUNLIGHT READABLE
- LONG LIFE LOW POWER CONSUMPTION LED BACKLIGHT
- AR GLASS WITH OPTICAL BONDING
- IP65 WATERPROOF FRONT PANEL



SPECIFICATIONS

Display Type	15" Color TFT Active Matrix LCD
Native Resolution	1024 x 768 (XGA)
Viewing Angle	+/- 80 All Directons
Display Colors	16.2 Million
Active Area	304.128(H) x 228.096(V) mm
Pixel Pitch	0.297(H) x 0.297(V) mm
Luminance	1000 cd/m2 Typical w/ LED Backlights,
Contrast Ratio	700:1 Typical
Response Time	25 ms Typical
Front Controls	Power
Video Input	DVI-D, VGA (HD15F), Composite 3x
Power	Voltage: 9-36V DC Input Power: <45 Watts Typical

ENVIRONMENTAL / MECHANICALS

Temperature	Operating:	-15C to 55C
	Storage:	-20C to 70C
Physicals	Height:	12.00 inches
	Width:	14.00 inches
	Depth:	2.20 inches
	Weight:	<8 pounds
Mounting	Panel Mount / VESA Mount	
Options	Resistive Touch (USB)	
Approval	IEC 60945	

